


SPECIFICATIONS



ColorFlex[®] L2

MEASUREMENT

Measurement Principle:	Port up or Port forward dual-beam spectrophotometer
Geometry:	45°/0° Annular Illuminated Optics, ASTM E1164
Spectrophotometer:	Sealed optics; 256-element diode array and a high resolution concave holographic grating
Port Diameter/View Diameter:	31.8 mm (1.25 in) illuminated/ 25.4 mm (1 in) measured
Specular Component:	Excluded
Spectral Range:	Range: 400 nm - 700 nm
Spectral Resolution:	< 3 nm
Effective Bandwidth:	10 nm equivalent triangular
Reporting Interval:	10 nm
Photometric Range:	0 to 150 %
Light Source:	Full spectrum Xenon Flash Lamp
Measurement Duration:	1 second
Lamp Life:	10 years typical
UV Content:	Calibrated, Fixed UV Content Level
Standards Conformance:	CIE 15:2018, ASTM E1164, DIN 5033, Teil 7 and JIS Z 8722 Condition C
Standards Traceability:	Instrument standard assignment in accordance with National Institute of Standards and Technology (NIST) following practices described in CIE Publication 44 and ASTM E259

PERFORMANCE

Inter-Instrument Agreement:	Color: $\Delta E^*_{2000} < 0.15$ D65/10 (Avg) on BCRA CCSII Tile
Colorimetric Repeatability:	Color: $\Delta E^*_{2000} < 0.03$ D65/10 (Max) on White Tile



FIRMWARE

Data Views:	Color Data, Spectral Plot, EZ View, Tristimulus Color Plot, Pass/Fail Color Indication, Time, and Date Stamp, Auto-naming, Auto-saving, Data backup and recovery, Image Capture via High-resolution Camera
USB Flash Drive Features:	Backup of WorkSpaces and Jobs, Transfer WorkSpaces to Multiple Instruments, Data Export to Excel
Other Features:	Pass/Fail, Average Multiple Measurements, Search for Closest Standard, Set Multiple Automatic Measurements
Illuminants:	A, C, D50, D55, D65, D75, F02, F07, F11
Observers:	2° and 10°
Color Scales:	CIE L*a*b*, Hunter Lab, CIE L*C*h*, CIE Yxy, CIE XYZ, Rd,a,b
Color Difference Scales:	$\Delta L^*a^*b^*$, ΔLab , $\Delta L^*C^*h^*$, ΔYxy , ΔXYZ
Color Difference Indices:	ΔE , ΔE^* , ΔE^*2000 , ΔH^* , ΔC^* , ΔE_{cmc}
Indices and Metrics:	E313 Whiteness and Tint (C/2° or D65/10°), E313 Yellowness (C/2° or D65/10°), D1925 Yellowness (C/2°), Y Brightness, Z%, 457 nm Brightness, Opacity, Color Strength (Average and Single Wavelength), Gray Scale, Gray Stain, Metamerism Index
Data Storage:	1 million Records max; 8 GB
Languages:	English, German, Traditional and Simplified Chinese, Spanish

PHYSICAL / ELECTRICAL

Dimensions:	Height: 16 cm (6.25 in.) Width: 21 cm (8.75 in.) Depth: 24 cm (9.50 in.) Weight: 2.75 kg (6 lbs)
Display:	7" Touch screen, high resolution 1280x800
Interface:	2 USB ports, HDMI Video Output, Foot switch Input, Ethernet connection, USB Service Port, Convenient physical measurement/action button
Power:	90 – 240 VAC, 47 – 63 Hz to universal power supply @ 24 VDC/3.75A
Operating Environment:	10° to 30°C (50° to 86° F), 10 % to 90 % RH, noncondensing
Storage Environment:	-20° to 65°C (-4° to 149° F), 10 % to 90 % RH, noncondensing
Standard Accessories:	<ul style="list-style-type: none"> • Calibrated Instrument Standard (White Tile) • Diagnostic Check Tile (Green Tile) • Reflectance Black Glass • Port Plate - 25 mm (1 in) • Certificate of Traceability • Power Supply • Quick Start Guide • Built in Help Menus and Wizards

For more information, please contact HunterLab at 703-471-6870, sales@hunterlab.com or visit www.hunterlab.com